LRD-TL TRIMLESS RECESSED



TECHNICAL SPECIFICATIONS:

- :: Die-cast aluminum with white powder coat finish
- :: CRI: 90
- :: Working voltage: 120V AC
- :: Lumens: 700LM
- :: Beam Angle: 30°
- :: Dimmable down to 10% using a standard TRIAC LED dimmer
- :: Power factor: 90% +
- :: Suitable for damp locations
- :: Maximum Ambient Temperature: 104°F
- :: 5-year warranty
- :: ETL-listed
- :: Energy Star certified



















LED TRIMLESS RECESSED LIGHTS - 4"

CATALOG NO.	SHAI	PE	WATTAGE		COLOR TEMPERATURES		TRIM FINISH	
LRD-TL	R R	OUND	10W	10W	27K	2700K	WH	WHITE
	s s	QUARE			30K	3000K	ВК	BLACK
					35K	3500K	C	CLEAR
					40K	4000K	MG	MATTE GOLD
					50K	5000K	HZ	MATTE SILVER
	SAMPLE ORDE	RING:						

LRD-TL-S-10W-40K-BK

TECHNICAL SPECIFICATIONS:

:: Die-cast aluminum with white powder

:: Lumens: 700LM (10W), 500LM (7W) :: Beam Angle: 10° (pin hole & slot trims)

:: Maximum Ambient Temperature: 104°F

:: Dimmable down to 10% using a standard TRIAC LED dimmer

:: Working voltage: 120V AC

24° (open trims)

:: Power factor: 90% + :: Suitable for damp locations

:: Energy Star certified

:: 5-year warranty :: ETL-listed

LRD **WINGED RECESSED**



Open













coat finish :: CRI: 90









Matte Gold





Black on Black













LED WINGED RECESSED LIGHTS - 3"

CATALOG NO. WATTAGE		COLOR TEMPERATURES		TRIM (ADJUSTBLE)		TRIM FINISH		
LRD	7W	7W	27K	2700K	WTR	OPEN TRIM	WH	WHITE (ALL TRIMS)
	10W	10W	30K	3000K	WTRPH	PIN HOLE TRIM	BK	BLACK (ALL TRIMS)
			35K	3500K	WTRSL	SLOT TRIM	ABK	BLACK ON BALCK (OPEN TRIMS ONLY)
			40K	4000K			C	CLEAR (OPEN TRIMS ONLY)
			50K	5000K			MG	MATTE GOLD (OPEN TRIMS ONLY)
SA	AMPLE O	RDERING:					HZ	MATTE SILVER (OPEN TRIMS ONLY)
L	RD-7V	V-30K-	WTR-	MG				

WESTGATE MFG